



**WACKER
NEUSON**

Search

- [Locations](#)
- [New Products](#)
- [Manuals](#)
- [Spare Parts](#)
- [Machines](#)
- [FAQs](#)
- [Current Promotions](#)
- [Request a Product Demo](#)

Home > Product Guide - Machines > View All Models > **M 2000**

M 2000
115 V Electrical Power Unit for Internal Vibrator
 Item Number 0007159

Economical concrete consolidation for every need

The electrically driven HMS system is extremely versatile. These high frequency flex-shaft internal vibrators can be adapted to every type of application. Heads and shafts can be easily combined and rapidly exchanged to match the right equipment to the job. Unique hybrid heads offer optimum concrete consolidation and movement. WACKER HMS systems provide reliable performance and quality concrete.



- [Accessories](#)
- [Manuals](#)
- [Spare Parts for this Model](#)
- [Technical Data](#)
- [Standard Package](#)
- [Printer Friendly Version](#)
- [Request a Demonstration](#)
- [Features and Benefits](#)

Accessories – M 2000

Accessories are not included with machine purchase.



Carrying strap
0085738

[Top](#) | [Accessories](#) | [Technical Data](#) | [Features and Benefits](#) | [Manuals](#) | [Standard Package](#)

Technical Data – M 2000

Description	Metric	Imperial
Power Source	Universal electric motor	
Max. power output according to DIN-ISO 3046*	1,7 kW	2.3 hp
Voltage	115 V	115 V
Rated amperage	15 A	15 A
Frequency	50-60 Hz	50-60 Hz
Speed no-load	17.500 1/min	17,500 rpm
Overall size l x w x h	350 x 160 x 200 mm	13.75 x 6.25 x 8 in
Weight	5,9 kg	13 lb
Shipping size	430 x 180 x 255 mm	17 x 7 x 10 in

Owens Supply Co. Plainfield (chicago), Il. 1-866-566-7151

Shipping weight
(including
packaging)

7 kg

15.5 lb

Specifications may change due to continuous product development.
* Actual power output may vary due to conditions of specific use.



[Top](#) | [Accessories](#) | [Technical Data](#) | [Features and Benefits](#) | [Manuals](#) | [Standard Package](#)

Features and Benefits – M 2000

- Lightweight, but rugged unit preferred by operators.
- Double insulated and grounded motor improves safety.
- Dual air filters extend motor life and allow for easier maintenance.
- High frequency and amplitude of the vibrator head on the Head, Motor, Shaft (HMS) System ensures more complete consolidation of concrete.
- Motor airflow from rear to front prevents dust buildup that would otherwise cause motor damage.
- Standard quick disconnect coupling on motor facilitates shaft exchange. No troublesome threading or stripping.
- Quick release brush covers simplifies brush replacements.
- Dust and waterproof on-off switch eliminates burnout and damage.
- Strain relieved electrical cord inhibits cord pull out, reducing downtime.
- Integrated quick disconnect couplings on shafts easily connect to all WACKER motors, offering 62 combinations.
- Circuit breaking carbon brushes stop motor when replacement is required.
- Standard 60 Hz electrical power.

[Top](#) | [Accessories](#) | [Technical Data](#) | [Features and Benefits](#) | [Manuals](#) | [Standard Package](#)

Manuals – M 2000

-  [Operator's Manual](#) File Size: 2.05 MB
-  [Parts Manual](#) File Size: 3.45 MB

[Top](#) | [Accessories](#) | [Technical Data](#) | [Features and Benefits](#) | [Manuals](#) | [Standard Package](#)

Standard Package – M 2000

- includes operator's manual and parts book

[Top](#) | [Accessories](#) | [Technical Data](#) | [Features and Benefits](#) | [Manuals](#) | [Standard Package](#)

 [Top](#)

[Site Map](#) | [Contact](#) | [Help](#) | [Home](#) | [Search](#) | [Imprint - Site Policies](#)
© 2008 Wacker Construction Equipment AG